


H6-7XD-EC3-4 SERIES




EMPTY CONTAINER HANDLER PRODUCT TECHNICAL GUIDE






- = Centre of gravity of unladen truck
- $A_{ST} = b_{13} + b_{12}/2 ((l_6+x)^2 + (b_{12}/2-b_{13})^{0.5} + a$
- b_{12} = load width
- l_6 = load lengths
- a = Minimum operating clearance = 10% of A_{ST}
(VDI standard = 200 mm BITA recommendation = 300 mm)



- = Centre of gravity of unladen truck
- $A_{ST} = b_{13} + b_{12}/2 ((l_6+x)^2 + (b_{12}/2-b_{13})^{0.5} + a$
- b_{12} = load width
- l_6 = load lengths
- a = Minimum operating clearance = 10% of A_{ST}
(VDI standard = 200 mm BITA recommendation = 300 mm)

RATED CAPACITIES AND STACKING HEIGHTS



GENERAL	1.1		HYSTER				
	1.2	Manufacturer's type designation		H6XD-EC3	H7XD-EC4		
1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Diesel				
1.4	Operator type: hand, pedestrian, standing, seated, orderpicker		Seated				
1.5	Rated capacity / rated load	Q	kg	6,000	7,000		
1.6	Load centre distance	c	mm	1,220			
1.8	Load distance (588 TB spreader / 586 TB spreader)	x	mm	1,133 / 1,210			
1.9	Wheelbase	y	mm	3,300			
1.10.1	Stacking height at first row (number x container height, in feet)			3 x 8'6"	4 x 8'6"		
1.10.2	Stacking height at first row (number x container height, in feet)			3 x 9'6"	4 x 9'6"		
WEIGHT	2.1	Service weight (1)		kg	22,110	24,450	
	2.2	Axle loading with load, front / rear		kg	23,764 / 4,345	29,947 / 4,593	
	2.3	Axle loading without load, front / rear		kg	13,486 / 8,624	14,955 / 9,584	
WHEELS	3.1	Tyres: L = Pneumatic, V = Solid, SE = Pneumatic Shape Solid		L			
	3.2	Tyre size, front		12.00-20 20PR			
	3.3	Tyre size, rear		12.00-20 20PR			
	3.5	Wheels, number front / rear (x = driven wheels)		4x / 2			
	3.6	Track width, front	b ₁₀	mm	1,842	2,469	
3.7	Track width, rear	b ₁₁	mm	2,018			
DIMENSIONS	4.1	Mast tilt, forward / backward		α/β	deg		5° / 6°
	4.2	Height of mast lowered (unloaded)		h ₁	mm	5,193	6,693
	4.3	Free lift		h ₂	mm	0	
	4.4.1	Spreader distance from ground to twistlocks, minimum.		h _{3.1.1}	mm	2,151	
	4.4.2	Spreader distance from ground to twistlocks, maximum.		h _{3.1.2}	mm	9,061	12,061
	4.5	Height of mast, extended (unloaded) - top of spreader		h ₄	mm	9,459	12,459
	4.7	Height of overhead guard (open cab)		h ₆	mm	3,083	
	4.7.1	Height of overhead guard (closed cab)		h ₆	mm	3,110	
	4.7.2	Height of overhead guard (closed cab w/ aircon)		h ₆	mm	3,110	
	4.7.3	Height of overhead guard (closed cab w/ strobe light)		h ₆	mm	3,205	
	4.7.4	Height of overhead guard (closed cab w/ work lights)		h ₆	mm	3,259	
	4.7.5	Height of overhead guard (closed cab w/ aircon & strobe light)		h ₆	mm	3,235	
	4.8	Seat height to (Seat Index Point, ISO 5353)		h ₇	mm	1,903	
	4.12	Coupling height		h ₁₀	mm	689	
	4.16	Overhang		l ₅	mm	795	
	4.19	Overall length (588 TB spreader / 586 TB spreader)		l ₁	mm	5,441 / 5,518	
	4.20	Length to face of side lift spreader (588 TB spreader / 586 TB spreader)		l ₂	mm	5,228 / 5,305	
	4.21	Overall width truck		b ₂	mm	2,541	
	4.24	Attachment width, retracted/extended		b ₃	mm	6,106 / 12,238	
	4.30	Sideshift		b ₈	mm	400	
	4.31	Ground clearance, under mast (w/o load)		m ₁	mm	245	
4.32	Ground clearance, centre of wheelbase		m ₂	mm	341		
4.33	Aisle width with 20' container without operating clearance (588 TB / 586 TB)		Ast 20	mm	8,796 / 8,887		
4.33.1	Aisle width with 20' container with 200 mm operating clearance (588 TB / 586 TB)		Ast 20	mm	8,996 / 9,087		
4.33.2	Aisle width with 20' container with 10% operating clearance (588 TB / 586 TB)		Ast 20	mm	9,676 / 9,776		
4.34	Aisle width with 40' container without operating clearance (588 TB / 586 TB)		Ast 40	mm	13,583 / 13,645		
4.34.1	Aisle width with 40' container with 200 mm operating clearance (588 TB / 586 TB)		Ast 40	mm	13,783 / 13,845		
4.34.1	Aisle width with 40' container with 10% operating clearance (588 TB / 586 TB)		Ast 40	mm	14,942 / 15,009		
4.35	Outside turning radius		Wa	mm	4,637		
4.36	Internal turning radius		b ₁₃	mm	1,890		
PERFORMANCE	5.1.2	Travel speed laden/unladen Stage V (2)		km/h	27.4 / 29.0		
	5.2.4	Lifting speed laden/unladen 111cc Stage V		m/s	0.58 / 0.60		
	5.3	Lowering speed laden/unladen		m/s	0.50 / 0.48		
	5.5.2	Drawbar pull laden/unladen @ 1.6 km/hour Stage V		kN	109 / 110		
	5.6.2	Drawbar pull laden/unladen @ stall Stage V		kN	122 / 123	121 / 122	
5.7.2	Gradeability laden/unladen @ 1.6 km/hour Stage V		%	42 / 36	37 / 35		
5.8.2	Gradeability laden/unladen @ stall Stage V		%	48 / 36	42 / 35		

GENERAL	1.1	Manufacturer		HYSTER		
	1.2	Model designation		H6XD-EC3 / H7XD-EC4		
	1.3	Powertrain / drivetrain		Diesel		
ENGINE	7.1	Engine manufacturer / model		MTU OM 934 Stage V		
	7.2	Engine output according to ISO 1585 nominal		kW@rpm	129@2200	
	7.2.1	Engine power output - rated		kW@rpm	129@1800	
	7.2.2	Engine power output - peak		Nm@rpm	750@1600	
	7.3	Engine torque @rpm (1/min)		rpm	2,200	
	7.4	Number of cylinders / displacement		# / cm3	4 / 5300	
	7.8	Alternator output		Amps	120	
	7.10	Battery voltage, rated capacity		V / Ah	24 / 102	
DRIVETRAIN	8.1	Type of drive unit		Type	Torque Converter	
	8.2	Transmission Manufacturer / Type		Type	ZF / 3WG161	
	8.3	Drive axle Manufacturer / Type		#	Kessler D81	
	8.4	Service brake		Type	Oil immersed disc	
	8.5	Parking brake		Type	Dry disc on drive axle	
MISC	10.1	Operating pressure for attachments		bar	14.0	
	10.2	Oil volume for attachments		l/m	100	
	10.3	Hydraulic tank capacity		l	109	
	10.4	Fuel tank capacity		l	187	
	10.4.1	DEF Tank capacity		l	19	
	10.5	Steering design		Type	Hydraulic power steering	
	10.6	Number of steering rotations		#	5.0	
	10.7	Sound pressure level at driver's seat (3)		Lpaz	dB(A)	TBD
	10.7.1	Sound power level during the working cycle (3)		Lwaz	dB(A)	105.1
	10.8	Towing coupling, model / type		Yes / Pin		

MAST AND CAPACITY INFORMATION

	Spreader distance from ground to twistlocks max h _{3.1.2} (mm)	Lift height BOF h ₁ (mm)	Overall lowered height h ₁ (mm)	Overall extended height h ₄ (mm) Top of spreader	586 TB Spreader (kg)		588 TB Spreader (kg)	
					H6XD-EC3	H7XD-EC4	H6XD-EC3	H7XD-EC4
EC3	9,459	6,910	5,193	9,459	6,000	-	6,000	-
EC4	12,061	9,910	6,693	12,459	-	7,000	-	7,000

NOTES:

Specifications are affected by the condition of the vehicle and how it is equipped, as well as the nature and condition of the operating area. Inform your dealer of the nature and condition of the intended operating area when purchasing your Hyster® truck.

- (1) Based on Stage V engine and and 588TB spreader
- (2) Travel speed laden/unladen limited at 25 km/h as factory default
- (3) Based on low mount exhaust

All capacities are according to EN1551. All specifications and capacities are valid for trucks equipped with a Hyster® container handling spreader for handling ISO containers.

NOTICE:


Care must be exercised when handling elevated loads. Operators must be trained and must read, understand and follow the instructions contained in the Operating Manual. All values are nominal values and they are subject to tolerances. For further information, please contact the manufacturer.

Hyster products are subject to change without notice.

Lift trucks illustrated may feature optional equipment. Values may vary with alternative configurations.

CERTIFICATION: Hyster lift trucks meet the design and construction requirements of B56.1-1969, per OSHA Section 1910.178(a)(2), and also comply with the B56.1 revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

NOTE: Specifications, unless otherwise listed, are for a standard truck without optional equipment.

 **Safety:** This truck conforms to the current EU and ANSI requirements.

STANDARD AND OPTIONAL EQUIPMENT

PERFORMANCE	STD	OPT
Mercedes MTU Stage V Diesel Engine	X	
Stage V compliant	X	
Delayed Engine Shutdown for Turbo Cooldown	X	
Hydraulic driven cooling fan	X	
Performance modes	X	
Powertrain protection system	X	
Heavy duty air intake	X	
Heavy duty air intake (raised)		X
Low mount exhaust (below chassis)	X	
High mount exhaust		X
ZF Transmission WG161 3-speeds fwd/3-speeds reverse auto-shifting	X	
Kessler drive axle with wet disc brakes	X	
DRIVE	STD	OPT
Travel speed limiter - unconditional and customer adjustable		X
Travel speed limiter when carrying container (adjustable)		X
12.00 - 20 20PR Trelleborg Pneumatic Bias Ply drive and steer tyres	X	
12.00 - R20 Michelin XZM Radial drive and steer tyres		X
12.00 - R20 Trelleborg Radial drive and steer tyres		X
12.00 - 20 Pneumatic Shaped Solid drive and steer tyres		X
Spare wheels and tyres		X
LIFT	STD	OPT
111cc Dual Pump Hydraulic System	X	
On-Demand Load Sensing Hydraulic System	X	
Automatic Throttle-up when lifting (in neutral or inching)	X	
2 Stage Non Free Lift mast	X	
Mast tilt - 5° Forward / 6° Back	X	
Mast Tilt Indicator - Mechanical		X
Hydraulic Accumulator		X
Pressure compensated lowering	X	
Hydraulic system temperature protection		X
HANDLING	STD	OPT
Hyster 586TB single spreader, with removable blocks for ISO or wide containers		X
Hyster Model 588TB single spreader	X	
CANBus spreader controls	X	
Mechanical Pile Slope	X	
+/- 15/7" (400mm) Sideshift	X	
ERGONOMICS	STD	OPT
Enclosed operator cabin	X	
Manual tilt operator compartment for service	X	
Powered tilt operator compartment for service		X
Isolated cabin mounting for low noise and vibration	X	
Operator presence system	X	
Mechanical suspension seat	X	
Air suspension seat		X
Deluxe air suspension seat		X

ERGONOMICS (continued)	STD	OPT
Low backrest seat	X	
High backrest seat		X
Armrest on left side	X	
Cloth seat cover	X	
Vinyl seat cover		X
Seat heating		X
Seat ventilation		X
2-point high visibility seatbelt	X	
3-point high visibility seatbelt		X
Lateral seat sliding mechanism		X
Floor mat	X	
Coat hook	X	
Front, top and rear wipers with individual controlled washers	X	
"H"-pattern front wiper (Enclosed operator cabin)		X
"I"-pattern front wiper (Enclosed operator cabin)	X	
Intermittent wipers	X	
Top window with armoured glass (Enclosed operator cabin)	X	
Steel bars under armoured glass top window (Enclosed operator cabin)		X
Tinted operator compartment windows (all)		X
Tinted operator compartment top window		X
Right side door	X	
Wire mesh installed on top of operator compartment		X
7" Integrated Performance Display	X	
Joystick hydraulic control integrated in Control Arm	X	
Steering wheel with spinner knob	X	
Directional control lever on steering column		X
Directional control on joystick	X	
Park brake - push button applied	X	
Park brake - automatically applied		X
Heater with adjustable speed fan (Enclosed operator cabin)	X	
Diesel fueled cabin heater		X
Telescoping and tilting steering column	X	
USB outlet inside armrest	X	
24-12 volt DC converter with 1 socket and 2 USB outlets		X
24-12 volt DC converter with 2 sockets and 2 USB outlets		X
DC/DC converter 24 volt/12 volt 2nd 12 volt socket		X
Automatic climate control		X
Reading light		X
Sun shades on top and rear		X
Sun visors front window		X
Trainer seat		X
Recirculation fan		X
Accessory mounting post		X
Accessory mounting bracket on cab front right pillar		X
Heated top- and/or rear window		X
Radio preparation set-up (wiring, two speakers and antenna)		X
Bluetooth Radio With 2 Speakers And Antenna		X

VISIBILITY	STD	OPT
Interior wide angle mirrors	X	
Exterior mirrors mounted to cab		X
Rear view camera system		X
Radar object detection system		X
Halogen work lights	X	
LED work lights		X
High Performance LED work lights		X
Two head lights mounted on front fenders	X	
Four forward work lights mounted on the cabin	X	
Two rearward work lights mounted on the cabin	X	
LED twistlock indicator lights	X	
LED stop/tail/brake lights	X	
Turn signals, hazard & marker lights (LED)	X	
OPERATION	STD	OPT
Air horn 112 dBA		X
Electric horn 105 dBA	X	
Visible alarm - Amber strobe light, ignition activated	X	
Audible alarm - Reverse direction activated 82-102 dB(A), self-adjusting		X
Audible alarm - Reverse direction white noise		X
Blue LED spotlight - rear / front and rear		X
Hydraulic load weighing system		X
Tire pressure monitoring system		X
Air conditioning shut-off with open door		X
Automatic engine shutdown with timer		X
Lockable battery disconnect switch		X
Battery jump start connector (NATO plug)		X
Truck Start with key switch and start button	X	
Operator password (display) for Truck Start		X
Seatbelt Interlock for truck start		X
Fuses Below 30 amps Replaced by Electric Circuit Breakers		X
Non-lockable fuel cap	X	
Lockable fuel cap		X
Diesel fuel inlet strainer in filler neck		X
Hyster Tracker wireless asset management system		X
Hyster Tracker wireless asset management - Access / Verification		X
Hyster Tracker wireless asset management - Monitoring		X
Auto greasing system for basic truck and outer mast		X
24 volt electrical system	X	
Steer wheel lug nut protection		X
Front mud flaps		X
Rear mud flaps		X
4 Lifting eyes - 2 front and 2 rear		X

*Standard or Optional in select markets or on select models.
Other options available through Special Products Engineering Department (SPED). Contact Hyster for details.

STANDARD AND OPTIONAL EQUIPMENT

APPEARANCE	STD	OPT
Hyster yellow paint base truck	X	
Special paint base truck		X
Operator compartment special paint (outside only)		X
Hazard warning striping on counterweight		X
SUPPLEMENTAL	STD	OPT
Literature package	X	
Operator's manual	X	
CE certification *	X	
Warranty: 24 Months / 4,000 Hours *	X	
Warranty: 12 Months / 2,000 Hours *		X



CE UK
CA

Reg no. 10004925



HYSTER EUROPE
Centennial House, Frimley Business Park, Frimley, Surrey, GU16 7SG, England.


 www.hyster.com  infoeurope@hyster.com  [/HysterEurope](https://www.facebook.com/HysterEurope)  [@HysterEurope](https://twitter.com/HysterEurope)  [/HysterEurope](https://www.youtube.com/HysterEurope)  [@hyster.europe](https://www.instagram.com/hyster.europe)  [/hyster-emea](https://www.linkedin.com/company/hyster-emea)

Visit us online at www.hyster.com or call us at **+44 (0) 1276 538500**.

HYSTER-YALE UK LIMITED trading as Hyster Europe.

Registered Address: Centennial House, Building 4.5, Frimley Business Park, Frimley, Surrey GU16 7SG, United Kingdom.

Registered in England and Wales. Company Registration Number: 02636775.

© HYSTER-YALE UK LIMITED. 2022, all rights reserved. Hyster and  are trademarks of Hyster-Yale Group, Inc.

Hyster products are subject to change without notice. Trucks may be shown with optional equipment.